# INTERIOR EQUIPMENT AND LAYOUTS



Version A Forward Owner's cabin 1 aft cabin / 2 heads

# **WOODWORK**

### Standard

 Alpi<sup>®</sup> Teck interior woodwork laminated with solid wood trim, UV stabilized varnish · Fully-upholstered hull sides and ceiling Ceruse light Oak laminate floorboards Options

• Woodwork in Alpi® grey Cedar mat finish, open-pore varnish

· Ceruse dark Oak laminate floorboards

# SALOON

# Standard

- Comfortable seating arrangement to starboard
- with view of sea though hull ports
- Hinged storage compartments under settee • Large storage between the saloon and
- the companion way
- Bottles storage
- Large storage behind backrests
- Large table with 2 removable aluminium legs
- Convertible berth in saloon
- Companionway with anti-sleep floor surface
- Wine storage locker under floorboards

#### Options

• "Luxe" folding table on telescopic legs or electric leg · Central two-seat bench with storage

## CHART TABLE

- Large chart table with leatherette worktop, opening compartment for laptop computer • Sofa in vis à vis at the chart table Book shelve
- Multiple storage for telephone, keys...
- Large storage space under electrical panel for books and other navigation equipment, storage underneath the seat
- Access to central cabinet storage compartment • Bicolour reading light
- · Ergonomic seat, seaworthy
- Opening port above the chart table

# GALLEY

## Standard

- U-shaped galley located on port side, with view on the sea
- Counter top in Corian<sup>®</sup>, with fiddles
- Double stainless steel sinks with chrome fixtures
- Large drawer in the centre cabinet
- Soft-close, fully-extending drawers
- Sliding waste bin 26 L / 7 US gal • Open storage behind the galley
- 2 burner stove with protective handrail
- Fridge 190 L / 50 US gal with top opening

# Options

• Push up micro wave • Extra fridge drawer 75 L / 20 US gal • Extra freezer drawer 75 L / 20 US gal



## Standard

• Cushions in High Density foam 140 mm in the salon • High Density Premium mattresses in cabins

## Ontions

 Cruisair<sup>®</sup> air conditioning working from generator or shore power with 3 units (40 000 BTU in total) • Pushed air heating system 11 000 W with outlets in each cabin and head

## FORWARD OWNER'S CABIN (versions A, B and E)

- Standard
- Large passageway
- Large domestic size, rectangular berth, 2,00 x 1,60 m / 6'6" x 5'2"
- · Large dressing locker to starboard with hanging locker, full height drawer, opening cabinet and LED lighting
- Large hanging locker to port
- Central book shelve with space for the optional TV · Lower locker with drawer, shoes storage and leatherette
- top finish
- 3 large drawers underneath the berth (2 drawers if air
- conditioning is selected) • Side bed tables with leatherette
- Fully upholstered front bulkhead
- $\boldsymbol{\cdot}$  Large mirror in front of the cabin
- LED lighting
- 2 opening deck hatches, for light and ventilation above the bed and 1 in the passageway
- 2 large fixed hull ports with sliding blinds · Deck hatches with blind and bug screens
- Separate toilet compartment to port, with GRP sink furniture, storage, hull port allowing sea view, opening deck hatch, indirect LED lighting, large marine toilet with
- manual pump • En-suite owner's head compartment, with direct access from the cabin, GRP sink furniture, drawer, opened storage shelves, hull port allowing sea view, opening deck hatch, indirect LED lighting, full height mirror. Separate shower compartment located in the centre of the boat for higher headroom, with its dedicated opening deck hatch and plexiglass door, shower, shower
- drain with automatic switch Options

## Mattrass battons

· Electric Quiet-Flush toilets, on fresh water circuit, in place of manual toilets

## AFT CABIN(S) (all versions)

- Large domestic size, rectangular berth 2,00 x 1,60 m /
- 6'6" x 5'2"
- Hanging locker storage and shelf along hull
- LED Lighting
- LED reading lights
- 1 long fixed hull port, 1 large fixed cockpit window • 1 opening port on coachroof, 1 opening port towards the
- cockpit, 1 opening port towards the side decks
- Blinds for each opening
- · Access to tanks and technical area behind the engine

SPBI JEANNEAU - 32 Avenue des Sables - CS 30529 - 85505 LES HERBIERS CEDEX - FRANCE - TEL +33 (0)2 51 64 20 20 - www.jeanneau.fr

# HEADROOM

Forward cabin(s)	1,88 m	6'2"	Compan
Aft cabin(s)	1,91 m	6'3"	Saloon

- 1.98 m 6'6" 2.00 m 6'7"
- Galley 1,92 m 6'4" Forward head 1,90 m 6'3"





**SPECIFICATIONS** 

Overall Length with bowsprit

14.42 m 47'3"

48'6''

45'11

43'5"

14'8"

7'4''

2 870 kg 6 327 lbs

3 213 kg 7 083 lbs

24 890 lbs

14,80 m

14,00 m

13,24 m

4,49 m

11 290 kg

2,24 m

1.65 m 5'4"

AN EXCEPTIONAL LEVEL OF EQUIPMENT

• High aspect ratio rig, cathedral mast and split rigging

· Boom with rigid boom vang and lowered gooseneck,

Discontinuous standing rigging, stainless steel wire

· Sheets lead back to the helm - German sheeting

· Large choice of sails sets and optional Performance mast

· Blinds for each hatch and opening in the forward and aft

· Large seaworthy storage spaces, with fiddles, soft closing

• Semi-battened mainsail and furling genoa with

Construction

traditional decks

lounging and manoeuvring

Cockpit

cahin

Galley

of the boat

Water System

Hot and cold cockpit shower

• "Heavy-duty" water pump

Chart table

wide books storage

Overall length

Hull length

Beam

Waterline length

Displacement light load

with deep draft keel

Standard keel draft

Standard keel weight

Shoal keel draft

Shoal keel weight

**EXTERIOR** 

• Harken® genoa tracks

• Harken® deck hardware

to ease manoeuvring

Lazy bag and lazy jacks

INTERIOR .

• LED lighting

cabins

Electrical

One-level interior with no door sills

• Leather-wrapped handrails

• Fully-upholstered hull sides

drawers and cabinets

• 12 V electrical panel

protect battery banks

TECHNICAL \_

• Battery Exide Dual Marine

• LED navigation and anchoring lights

• 125 Ah alternator and charge distributor/isolator

Positive and negative battery cut-off switches to better

· Large, rectangular double berths

· Large doors double access to aft head

• Numerous choices of interior ambiances

UV protection

• Harken<sup>®</sup> roof and primary winches

Anodised aluminium mast and boom

Sailing features

· Starboard aft head: double access, from starboard cabin and saloon. GRP sink furniture, storage with towel shelf. Teak shelf with fiddle, large roof window, opening port for light and ventilation, indirect LED lighting, shower, shower drain with automatic switch, water inlet valve and connector underneath the sink, large marine toilet with manual pump, hook, large mirror, shower separated with a plexiglass door on versions A and B

## I WORKSHOP ON PORT SIDF (version A)

· Workshop located on port side behind the chart table, double access from the interior and from the cockpit • LED lighting

- · Large fixed hull window
- Access to the tank

Version D

2 forward cabins

3 aft cabins / 3 heads

- Direct access to electrical panels
- Lateral storage locker

## PORT SIDE HEAD (version C)

• GRP sink furniture, storage with towel shelf. Teak shelf with fiddle, large roof window, opening port for light and ventilation, indirect LED lighting, shower, shower drain with automatic switch, water inlet valve and connector underneath the sink, large marine toilets with manual pump, hook, large mirror

## **PORT SIDE LATERAL CABIN** (versions D and F)

· 2 bunk beds, hanging locker, reading LED light, locker

underneath the inferior bed • Opening deck hatch for ventilation, fixed roof windows

#### TWIN FORWARD CABINS (versions C and D)

- Large rectangular berth 2,00 x 1,40/0,79 m /
- 6'6'' x 4'7''/2'7''
- Removable bulkhead between the cabins
- Hanging locker • Storage underneath the berth

• Opening deck hatch with ventilation

FORWARD HEADS

(versions C and D)

· Large fixed hull windows with sliding blinds

• Blinds and bugs screens for deck hatches

• GRP sink furniture, storage, hull port allowing sea view,

switch, water inlet valve and connector underneath the

opening deck hatch for light and ventilation, indirect

LED lighting, shower, shower drain with automatic

sink, large marine toilet with manual pump, hook

LED lighting





Fuel capacity	240 L	63 US gal	
Water capacity	640 L	169 US gal	
Fridge capacity	190 L	50 US gal	
Holding tank capacity	130 L	34 US gal	
Standard mainsail, horizontally-cut, in High Strength polyester	56,61 m²	609 Sq ft	
Standard 120 % genoa, horizontally-cut, in High Strength polyester	53,50 m²	577 Sq ft	
CE category 2-3 cabins layout	A9 / I	B10 / C14	
CE category 4-5 cabins layout	A13 /	A13 / B14 / C16	
Architect / Designer	Briand Yacht Design Piaton Yacht Design Jeanneau Design		

14 00 m

- Multi-function cockpit table · Leather-covered stainless steel steering wheels · Infused sandwich hull with balsa core and fiberglass skins, · Large aft fold-down swim platform with telescopic ladder ISO gelcoat surface, protective barrier coat Telescopic bath ladder Infused fiberglass inner liner, easy access to grounding • Hinged companionway doors frame, relamination in stays attachment areas. • Prisma Process® injected deck, ISO gelcoat, discontinuous Deck balsa block coring - 30% weight savings as compared to • Easy circulation thanks to the inclined side decks • Elush deck hatches • Twin rudders with self-aligning roller bearings and textile Long tinted acrylic roof windows lines, to increase control and pleasure in navigation • Split rigging: Inboard shrouds for easier access forward • External woodwork and inlays made of Teak Mid-ship cleats · Asymmetrical cockpit with dedicated area for dinning, Electric windlass • Walk-in access to side decks, enabling to walk around the deck without crossing any steps • Separated shower compartment in the forward owner's Corian<sup>®</sup> countertops Double stainless steel sinks • 2-burner stove with oven • Full-size mirrors in the owner's cabin and in the heads • Fridge 130 L / 34 US gal with top access to better maintain the cold air • Large navigation desk with leatherette lining and interior Woodwork storage for a portable computer, electrical panel, sofa and • Woodwork in Alpi® Teak or grey Cedar • UV stabilized varnish · Ceruse light or dark Oak laminate floorboards • U-shape galley, ideally located near the centre of gravity Numerous solid wood mouldings
- Hot water heater 40 L / 11 US gal

#### Engine

- Latest-generation Yanmar Common Rail Sail Drive engine with reduced CO2 emissions and consumption
- Fixed 3-blade propeller
- Sound insulation 40 mm / 1 ½" thick, with fire retardant film

TRIM LEVELS AND PACKS			
I TRIM LEVEL		"PREMIERE"	"PREFERENCE"
	Layout applicable	A, B, C, D, E	A. B
GRP bowsprit with integrated anchor roller (replaces the standard anchor roller)	.,	•	•
Second windlass control with chain counter, installed in the cockpit		•	•
Halyard bags in the cockpit with stainless steel frame (3)		•	•
40 Ah battery charger for 12 V battery banks		•	•
60 Ah battery charger for 12 V battery banks		٠	•
Additional service batteries (3 x 115 Ah / 12 V)		•	•
LED courtaisy lighting in the cockpit		•	•
3 burner cooker and oven with grill function (replaces standard 2 burner cooker)		•	•
Protective GRP eyebrow for the long acrylic roof windows		•	•
Navicolor battery monitoring		•	•
Upholstered bulkheads			•
Indirect LED lighting, and lamps on bulkheads			•
Shades for windows and ports in the saloon			•
Shades and screens for hatches in the saloon			•
Signature clock and barometer set at the chart table			•
Vertical door fridge			•
Specific compartment for cutlery in the central galley storage unit			•

# EXTERIOR AND TECHNICAL EQUIPMENT

## ARCHITECTURE

- Full-length hull chine for improved stability and speed • Long waterline for better speed while sailing and under power
- L-shaped cast iron keel less exposed to seaweed and lines
- Twin rudders with self-aligning roller bearings and textile lines, to increase control and pleasure in navigation

# SAILS

## Standard

• Horizontally-cut in high strength polyester • Semi-battened main sail with 3 reefs 56.61 m<sup>2</sup> / 609 Sq ft • 120 % furling genoa with UV protection 53,50 m² / 576 Sa ft

## Options

• In mast furling main sail horizontally-cut in high strength polyester 45,22 m² / 487 Sq ft • Self-tacking jib with UV protection in high strength polyester 37,82 m² / 407 Sq ft • Code 0 in triradial cross cut Mylar/Aramid laminate 93.6 m<sup>2</sup> / 1 007 Sq ft with continuous line furler (requires Downwind pack) Code 0 in triradial cross cut Mylar/Aramid laminate

for Performance mast 102,30 m² / 1 101 Sq ft with continuous line furler (requires Downwind pack)

# SAIL HANDLING

## Standard

- Mainsheet attached to Dyneema® bridle forward of companionway, with sheets led back to the cockpit winches
- Harken® genoa tracks with adjustable lead cars Spinlock<sup>®</sup> jammers
- Coachroof winch 1 x Harken® 46.2 ST to port • Genoa winches 2 x Harken® 50.2 ST winches for easy use at the helm stations
- Harken® winch handle

# Options

• Self-tacking jib ball bearing track on coachroof Electrical coachroof winch Harken<sup>®</sup> 46.2 ST • 2 x electrical primary winches Harken® 50.2 ST

# MAST AND RIGGING

- Standard · Classic aluminium mast with double spreaders, deckstepped, cathedral geometry and split rigging
- Aluminium boom with rigid vang and lowered goose neck for easier handling
- Double backstay • Genoa furler with double slot, furling line lead aft to
- cockpit on coach roof • Running rigging topping lift, mainsail halyard, genoa
- halyard, mainsheet, genoa sheets in polyester • Standing rigging discontinuous 1 x 19 stainless steel wire
- Asymmetrical lazy bag with integrated lazy jacks

#### Option

table

• Furling mast aluminium with double spreaders, deckstepped, cathedral geometry and split rigging

## 

## Standard

- Walk-in access to side decks, enabling to walk around the deck without crossing any steps.
- Large cockpit table with compass, cup holders, area for navigation instrument, cockpit light switch,
- handrails, LED lighting, bottle storage and optional portable fridge
- Teak inlay on bench seats, helms stations and transom platform
- Fixed coaming with ideal height for comfort and safety
- Cockpit lockers: 1 on starboard side, 1 on port side (versions B, C, D and E only), 1 large locker on the cockpit floor that can be used for the optional generator, one liferaft locker with open access to transom platform 92 x 65 x 48 cm / 3'00" x 2'1" x 1'6"
- Universal gas box, cut-off valve under the stove • Wheels with leather wrap, space for flush mounted GPS at each helm, stainless steel handrail, cup holders • Emergency tiller, and fitting in cockpit floor • Engine control: throttle lever at starboard helmstation and oriented engine panel on the cockpit

This document is non contractual and we reserve the right to modify equipment or specification without advance notice. Updated July 2020.

- · Large bathing platform with telescopic ladder,
- handrail and access step to the cockpit
- Hinged companionway doors in plexiglass • Sliding horizontal hatch in plexiglass
- · Cockpit table with stainless steel handrails

## Options

- Cockpit table with wooden leaves: replaces the standard table with all the same functions
- Teak inlay on cockpit floor
- Large cockpit sprayhood in Sunbrella®, high transparency windscreen and LED cockpit lighting
- · Cockpit Bimini with stainless steel bows in Sunbrella®, connecting fabric between Bimini and
- sprayhood
- Cockpit enclosure kit in Sunbrella®, fitted on the sprayhood and bimini
- Electrical bathing platform system with remote

## DECK HARDWARE

## Standard

- Bow pulpit in stainless steel
- · Stern pushpits in stainless steel with buoy bracket
- and emergency ladder
- Double level of stainless steel lifelines
- 6 aluminium mooring cleats • Stainless steel handrails on coachroof (2)
- Deep anchor locker
- Electric 12 V windlass 1 000 W 10 mm chain
- Long fixed tinted windows along coach roof
- Fixed cockpit windows in the aft cabins (2)
- Large, fixed hull ports (6)
- Opening ports in the roof (4)
- Opening deck flush hatches (11)
- Opening ports towards cockpit in the aft cabins (1 per cabin) · Opening ports towards side-deck in the aft cabins
- (1 per cabin)

# PACKS - ALL VERSIONS

## DOWNWIND PACK

 Spinnaker rigging with spinlock jammers · Halyards and sheet for asymmetrical spinnaker / Code O (2 polyester halyards, 1 sheet and 1 tack line in Dyneema®, pulleys on mast step and side decks) • Extra Harken® 46.2 ST winch to starboard on coachroof Extra winch handle • Windex 15" on mast head

## STARBOARD CONVERTIBLE COCKPIT PACK

· Extending starboard coaming convertible into lounging area • Exterior upholstery Sunbrella® • Cushions for starboard cockpit and sunbathing areas • Additional starboard cockpit seat cushion • Cushions for port side fixed cockpit Starboard lifelines' cushion • Helsman seat cushions

#### PORT SIDE CONVERTIBLE COCKPIT PACK

- Extending port side coaming convertible into lounging area • Exterior upholstery Sunbrella® • Cushions for port side cockpit and sunbathing areas Cushions for starboard fixed cockpit

LED lighting

- Port side lifelines' cushion
- Helsman seat cushions

Outboard engine bracket

## PACKS - VERSIONS "FORWARD OWNER'S CABIN" (A. B AND E) VOYAGER PACK

### PERFORMANCE PACK

- Downwind pack
- Tall anodised mast with 2 spreaders, cathedral
- geometry and split rigging
- Dyform standing rigging • Performance full-batten mainsail, triradial cut,
- in Flex<sup>®</sup> Lite Skin<sup>®</sup> 62,70 m<sup>2</sup> / 675 sq ft
- 120 % performance genoa, triradial cut, in Flex® Lite
- Skin<sup>®</sup> with UV protection 58,82 m<sup>2</sup> / 633 sq ft
- Harken® ball-bearing genoa lead cars and control
- lines lead to cockpit
- Dyneema<sup>®</sup> low-stretch halyards and sheets for main
- and genoa

Folding pulpits seating

Rubrail for hull protection

SAIL LOCKER

LIGHTING

Standard

cabin

Options

the transom

• Full LED interior lighting

FLECTRICAL

• 12 V engine alternator: 125 Ah

• USB plug in each cabin

• Access via lockable deck hatch

Access ladder in stainless steel

• Teak side-decks

Options

 Hydraulic textile adjustable backstay Composite steering wheels

· Lifeline gates with removable access ladder

• Anchoring kit with Delta 20 kg / 44 lbs, 32 m / 104'11"

Mooring kit 6 fenders and 4 docklines

of 10 mm chain and 45 m / 147'7" line

• Sunbed in Sunbrella® on the foredeck

• Main 12 V electrical panel at the chart table

• Domestic battery bank capacity 3 x 115 Ah / 12 V

• Positive and negative battery switch 12 V in the aft

• Engine start battery capacity 1 x 120 Ah / 12 V

• Lithium domestic battery bank 3 x 90 Ah / 12 V

appliance from the domestic battery bank

• Inverter 12 V > 220 V 2 000 W enable to use 220 V

• Generator Onan 7,5 KW 230V 2 400 rpm, located at

• 12V Circuit for house and engine system

#### Standard

FRESH WATER • Pressurised water distributed through-out the boat

PLUMBING

- via semi-rigid hose • "Heavy-duty" water pump 19 L / 5 US gal / mn,
- accumulator tank for consistent water pressure • Roto moulded tank: 400 L / 87 US gal, under the
- forward cabin berth
- cabin berth
- Tank gauges (1 per tank) Tank manifold with selector valves

GREY AND BLACK WATER

• Large bowl marine toilets

BILGES DRAINAGE

• Gas leakage detector

place of manual toilets

GAS

Options

• Water boiler 40 L / 11 US gal connected to the engine and 220 V circuit

#### **EXTERNAL GALLEY PACK**

- Cockpit sink with hot & cold water
- Portable 12 V fridge in the cockpit table

#### AUDIO ENTERTAINMENT PACK

- RA70N Fusion player (Radio / USB / Bluetooth/...) at the chart table
- Bose<sup>®</sup> speakers in the saloon
- Bose® subwoofer
- Speakers in the cockpit

### • High transparency sprayhood in Sunbrella® with

 Releasable forestay + deck fittings · Solar panel on coachroof with charging relay

## VIDEO ENTERTAINMENT PACK

- DVD player Fusion MS-AV755 (CD / DVD / USB / Bluetooth...) at the chart table
- · Bose<sup>®</sup> speakers in the saloon
- Bose<sup>®</sup> subwoofer
- Speakers in the cockpit
- TV LED 32" in the saloon
- DVD player Fusion MS-AV755 (CD / DVD / USB / Bluetooth...) in the forward owner's cabin
- TV LED 22" in the forward owner's cabin
- TV antenna for in mast fitting

• Roto moulded tank: 240 L / 53 US gal, under the aft

· Hot and cold cockpit shower on transom

· Automatic electrical shower self-activating

• Black water tank 50 L / 13 US gal, with gravity drain and deck fitting (forward and port aft heads) Black water tank 80 L / 21 US gal, with gravity drain and deck fitting (aft starboard head)

• Electric bilge pump located in bilge area with activation via switch at electrical panel

- Dual-action manual bilge pump located in the
- cockpit, with separate hose from primary bilge pump

# ENGINE

## Standard

- · Latest-generation Common Rail engine with reduced emissions and consumption
- Yanmar Engine 4JH57CR Sail Drive 57 HP / 42 kW -Alternator 125 Ah
- Engine panel oriented toward helmsman, located on the cockpit table. Throttle at helm station
- Insulation: Foam 40 mm, with fire retardant film
- Built-in muffler air ventilation and stainless steel exhaust fitting
- Fixed 3 blade propeller
- Ventilation system extractor fan located near the engine, benefiting from the insulation of the engine room. Outlets vents at the back of cockpit
- Roto moulded fuel tank 240 L / 63 US gal located under the aft cabin berth, fuel / water separator
- Access behind steps to engine compartment and from aft cabins

## Options

- Yanmar Engine 4JH80CR Sail Drive 80 HP / 59 kW - Alternator 125 Ah
- Extra fuel tank 240 L / 63 US gal, instead of a fresh water tank underneath the aft cabin berth
- Retractable bow thruster 6,3 kW 105 kgf (231,5 lbs) with a dedicated 12V battery bank and charger
- Retractable stern thruster 6,3 kW 105 kgf (231,5 lbs) with a dedicated 12V battery bank and charger
- Flex-o-fold 3 blade folding propeller

· Electric Quiet-Flush toilets, on fresh water circuit, in

. Water intake in the cockpit. Enable to connect the fresh water circuit directly to the shore